		Your Roll No
33	18	J
		B.Tech/III
	I	Paper ECE-301—DESIGN OF STRUCTURES
Tin	re :	3 Hours Maximum Marks: 70
		(Write your Roll No. on the top immediately
		on receipt of this question paper.)
		Question no. 1 is compulsory.
	Ans	swer <b>two</b> questions from Part A and <b>two</b> questions
from Part B. IS 456, SP16, IS3370, IS-800 and Steel		
		Tables are permitted. Draw neat sketches to
		illustrate your design.
I.	(a)	What are the advantages of Limit State Design over
		the other methods?
	<b>(b)</b>	Describe the method of design of Slender R.C.C. and
		Steel Columns. 4
	(c)	Describe the foundation for heavily loaded steel
		columns with sketches. How are they designed?
		4
	(d)	What are the stresses used for the limit state
		method of design of steel structures?
	ъ	Part A
Π.	Design a short column 700 × 500 mm subjected to P <sub>u</sub>	
		200 KN, $M_{ux} = 180$ kNm and $M_{uy} = 110$ kNm. Use 25 concrete and Fe 415 steel.
	478 6	.•
		IP Tr O

[This question paper contains 3 printed pages.]


III. A column 350 × 350 mm has to carry an axial load of 1050 kN (factored). The bearing capacity of soil 120 kN/m², unit weight of soil 14 kN/m³ and angle of repose of soil is 32°. Design a suitable isolated footing for the column. Use M 25 concrete and Fe 415 steel. Design for moment, one way sheat, punching sheat and bond.

IV. Design a rectangular water tank for a capacity 120000 litre resting on ground. The tank is continuous at bottom and free at the top. Use M 20 concrete and Fe 415 steel.

13

## Part B

- V. (a) What are the relative merits of welded and bolted connections?
  - (b) Two bracket plates are welded to both sides of ISHB 300 as shown in fig. Calculate the size of weld required to support a total load of 200 kN. 11



- VI. 4 angles  $200 \times 200 \times 12$  are used to make a column  $800 \times 800$ , 8 m high fixed at both ends. Determine the axial load it can carry. Design a suitable batten plate for the column.
- VII. (a) What are laterally restrained beams?
  - (b) Determine the moment carrying capacity of a laterally unrestrained beam ISMB 500 for a span of 5 m.